# MITS AIR<sup>®</sup>

## Mits Air<sup>™</sup> Side Discharge Inverter Air Conditioner



- Slim cooling solution for narrow spaces
- Reduces operating costs up to 40%
- / Ultra quiet operation
- From 12,000 to 24,000 btuh
- ✓ Up to 20 SEER



### www.mitsair.com

Outdoor Mode	el+		MOBA30-11CFN1-MQ0W	MOBA30-17CFN1-MROW	MOX330-22CFN1-MT0W
Power supply		Ph-V-Hz	208-230V, 1Ph, 60Hz	208-230V, 1Ph, 60Hz	208-230V, 1Ph, 60Hz
	Capacity	Btu/h	11500	17000	22000
Cooling	Input	w	1037	1583	1960
	Rated current	A	4.5	6.7	9.0
	EER <sup>§</sup>	Btu/w	11.1	10.8	10.9
	SEER <sup>§</sup>	Btu/w	19	20	19
Minimum Circuit Ampacity		A	11	15	18
Max. Fuse		А	15	20	25
Compressor	Туре		INVERTER	INVERTER	INVERTER
	Rated current (RLA)	A	6.8	9 -	12.0
Outdoor fan motor RLA		А	0.39	0.39	0.6
Outdoor noise level		dB(A)	51.5	53.5	57
Outdoor unit	Dimension(W*D*H)	Inch	30.31 x 11.81 x 21.85	30.31 x 11.81 x 21.85	33.27 x 14.29 x 27.64
	Net/Gross weight	lbs.	54.67/59.52	65.92/72.31	88.62/95.90
Refrigerant type (Precharge)		oz	R410A (18.7)	R410A_(31.7)	R410 <u>A (</u> 40.9)
Refrigerant precharge		ft	20	20	30
Additional charge for each ft		oz	0.21	0.21	0.32
Refrigerant piping	Liquid side/Gas side	Inch	1/4 <u>1</u> 1/2"	1/4 <u>" /</u> 1/2"	3/8 <u>" /</u> 5/8"
	Max. Refrigerant pipe length	ft	82	98	98
	Max. Difference in level	ft	33	66	66
Operation Temperature	Outdoor_(cooling)	°C	-3 ~ 35	-3 ~ 35	-3 ~ 35
	Outdoor_(cooling)	°F	25 ~ 95	25 ~ 95	25~95

TECHNICAL DATA

All testing and values are per Manufacturer's testing and use of Manufacturer's coils. Outdoor unit includes interface module.

CONDENSER MODEL #	SIZE (TON)	BTU	V/Ph/Hz	SEER**	EER	Outdoor Noise Level dB(A)	LINE SET SIZES <u>(Not Included)</u>
MOBA30-11CFN1-MQOW	1	11500	208-230/1/60	19	11.1	51.5	1⁄4" x 1⁄2"
MOBA30-17CFN1-MROW	1.5	17000	208-230/1/60	20	10.8	53.5	1⁄4° x 1⁄2°
MOX330-22CFN1-MTOW	2	22000	208-230/1/60	19	10.9	57	∛s" x %"

SEER Capacity depends on Indoor Unit.

#### WARRANTY:

Side Discharge Condenser by Mits Airconditioning Inc. - 5 years compressor, 5 year parts. Coil by ASPEN - 10 years, warranty registration required within 60 days of installation date, to upgrade to the 10 year warranty go to www.aspenmfg.com Thermostat by Comfort Stat - 5 years limited warranty.

All warranty is active from date of installation. Labour Warranty is the responsibility of the Installing Contractor. \*To register Mits Air warranty on equipment, go to www.mitsair.com/warranty-registration

Ν



lississauga	905-564-2221/800-567-2221				
Barrie	705-722-3200/800-688-1673				
London	519-914-9000				
Windsor	519-914-0332				

### www.mitsair.com